



BTS Remote Indicator

Detector indicator for addressable and non-addressable system applications

Description

BTS Remote Indicators provides visual alarm indication for addressable and non-addressable control and indicating equipment detectors when the detector connected to the remote indicator enters the alarm condition. The indicator is used to identify the detector in alarm and is useful where the detector cannot be easily seen when installed in the building.

BTS Remote Indicators provide fire detection and alarm system designers with an economical product for life safety and property protection applications.

Features

- Attractive design
- Easily seen when in the alarm condition
- Wide operating voltage
- Compatible with 2-wire addressable and non-addressable detectors
- Easy installation with no adjustments required
- Low maintenance



BTS Remote Indicator

Specifications

BTS-RLED-01	
Operating voltage	DC (5 ~ 36) V
Quiescent current	0 A
Alarm current (max)	20 mA
Terminal wiring	(0.4 ~ 2.5) mm ²
Operating temperature	(-20 ~ +60) °C
Operating humidity	(0 ~ 95) % RH, non-condensing
Storage temperature	(-25 ~ +80) °C
Storage humidity	(0 ~ 98) % RH, non-condensing
Dimensions	Φ 79 mm × 19 mm

Ordering Information

BTS-RLED-01

Distributed by: **BES Tech Solutions Pte Ltd**
421 Tagore Industrial Ave #03-08
Tagore 8 Singapore 787805
www.bes-tech.com.sg

BTS_RI_May2018